Security of EVSE and Electric Vehicles

Raju Gottumukkala, Ph.D

Director of Research, Informatics Research Institute
Site Director, NSF Center for Visual and Decision Informatics
Assistant Professor, College of Engineering

2017 Internet2 Global Summit (04/25/2017)










Charging a Plug-in Electric Car




AC charging

- Every vehicle has an on-board charger.
- Limited power, slow charging.

DC charging

- Infrastructure investment is shared among hundreds of users.
- Large power rating, fast charging.
- Capable of integration with renewable resources.


How Smart Charging Works?



Source: Lefrançois, Maxime, et al. "Outsourcing Electric Vehicle Smart Charging on the Web of Data." *Proceedings of the First International Conference on Green Communications, Computing and Technologies, (GREEN 2016), Nice, France.* 2016.

Cybersecurity vulnerabilities of connecting EV and EVSE

- RFID
- Zigbee
- RS-485
- CANBUS
- Key Fob
- Bluetooth
- Wi-Fi
- Cloud Security
- "People"





Source: http://thehackernews.com/2016/11/hacking-tesla-car.html





Charlie Miller • Chris Valasek • Work diligently since 2010 on DARPA funding • VIDEO DEMO Hacking Chrysler Jeep Remotely

Cybersecurity Testbed @ UL Lafayette



















1. Formal Methods for Modeling Integrative Cyber-physical systems

- Formal methods provides rigorous proofs that all the system behaviors (i.e. PEV's, EVSE, etc.)— so they can be reasoned for meeting desired properties
- Instead of a piecemeal strategy these methods rule out a range of possible entry points for attacks
- Formal methods have been successful in building systems with strong security properties such as control-flow integrity, memory safety and type safety [Chong 2016]
- Many formal modeling tools exist we are exploring CPN (Colored Petri nets)



2. Fingerprinting Algorithms to uniquely identify devices and vehicles



- The DSM system senses the closest EVSE using Bluetooth Energy
- DSM senses closest EVSE using Bluetooth Low Energy
- 3) DSM associates with EVSE using WPA-2 Protected WIFI
- 4) DSM sends security snapshot to EVSE
- 5) EVSE forwards security snapshot to BEMS
- 6) BEMS(or operator) makes decision to allow/deny charging
- 7) EVSE allows or denies charging

Expectations & Timeline

- How can you use this system?
 - Project outcomes:
 - Digital Security Modules for EVSE and Building Energy Management System Integration
 - Share the outcomes of the project with I2 community (with permission from INL & DOE)
 - Work with charging station manufacturers and PEV's to pilot this framework in few universities
- Plan for deployment
 - Evaluation will be complete early 2018
 - Development of DSM (2018 to 2019)

Thank You

Contact: raju@louisiana.edu

Homepage: www.ucs.louisiana.edu/~nrg0821