

Best Practices

This page provides best practices for InCommon library resource providers and libraries.

Comments are always welcome; please send a message to inc-library-vendor@incommonfederation.org.

Resource Providers

Resource providers deal with a variety of authentication challenges and often have to support several authentication schemes simultaneously. Shibboleth is just one of those schemes. These best practices should serve as a guideline for resource providers that are implementing Shibboleth. These best practices have been written by InCommon member institutions that have experience integrating Shibboleth as an authentication option for library resources.

If all of these best practices are followed, libraries will be able to maintain the seamless access they can currently provide with IP-based authentication, and also have the groundwork laid for future developments such as personalized services. As there are many resource providers and all have different platforms and services, there is no expectation that all will be able to implement these best practices immediately. Some items tend to naturally build on others and in those cases they have been listed sequentially below. Each issue is explored more deeply following the list.

1. Authorization via eduPerson attributes
2. Implement WAYFless URLs.
3. Implement authenticated direct links to resources.
4. Shibboleth/EZproxy hybrid compliance

Best practice #1: Authorization via eduPerson attributes

In a typical Shibboleth Single Sign On scenario, the Shibboleth identity provider (IdP) performs the authentication, and the service provider (SP) handles the authorization. The identity provider delivers (only) enough user attributes to the service provider so that the SP can make an informed authorization decision. These user attributes (their names and values) are completely variable in that they can be implemented in whatever format the identity provider and service provider agree to. However, there are standard definitions for how these attributes should be formulated, namely eduPerson.

One of the main values of a federation, such as InCommon, is an agreement to use a common set of user attributes. This simplifies implementation for both identity providers and service providers within the federation. InCommon strongly encourages the use of eduPerson attributes. For the purpose of this best practices document, the InCommon Library Services Collaboration makes more specific recommendations and as relates to the use of these (eduPerson) attributes, each party shares responsibilities vis a vis the other parties.

Libraries' responsibilities to e-resource vendors (Shibboleth SPs):

- to restrict the assignment of relevant entitlements to all (but ONLY) those members of their communities who meet the terms of licensing contracts with the vendors.

Libraries' responsibilities to their own users:

- to send only the amount of information about (only those attributes of) an individual as is necessary for the vendor to make a proper authorization decision
- to provide transparency to users about WHICH identity attributes are being released to any given SP (and when plausible, to actually allow user CONTROL over the attribute release). This becomes increasingly important as SPs move to support greater PERSONALIZATION features, since such features of their very nature REQUIRE the ability to identify an individual as an individual rather than simply as the member of a certain group or class.

E-resource vendors (SPs) responsibilities to libraries:

- to respect the agreed upon entitlements when they are presented during the authorization phase of attempted resource access. It is understood that this means that the agreed upon attribute must be released by the libraries' IdP and must contain an appropriate value.

In order for Shibboleth Single Sign On to be efficiently implemented across all vendors and libraries in the InCommon Federation, it is critical that there is standardization to the degree and in the ways that allows for the simplest solution that remains effective.

To this end, we strongly recommend the use of **eduPersonEntitlement** as the standard attribute used for authorization by e-resource vendors within InCommon. Furthermore, we strongly recommend that the relevant **VALUE** for the "eduPersonEntitlement" be "**urn:mace:dir:entitlement:common-lib-terms**" as described at <http://middleware.internet2.edu/urn-mace/urn-mace-dir-entitlement.html>*

By agreeing to and providing both a standard attribute and value:

- Libraries can efficiently manage access across scores of potential resources
- Vendors can efficiently manage access for scores of libraries

Best practice #3: Implement authenticated direct links to resources.

This is mainly an extension to best practice #2, WAYFless URLs. The difference though is that a resource provider can support WAYFless URLs even if those WAYFless URLs only work with their 'start page' or their search page. To support best practice #3, resource providers are asked to extend the WAYFless URL to work directly with resource URLs, so that WAYFless URLs can be created directly to a resource (ex. full text of an article).

Best practice #4: Shibboleth/EZproxy hybrid compliance.

EZproxy has the ability to rewrite URLs and redirect browsers appropriately. This ability allows EZproxy to be configured to generate WAYFless URLs for a target resource, if it is only given the target resource URL. What this enables for libraries is that they continue to send all of their links from other applications (link resolvers, metasearch engines, database of databases, learning management systems, etc) through EZproxy. And then EZproxy (when configured to do so) will turn those links into WAYFless URLs. This enables the institution to move to Shibboleth on a resource by resource basis, which is an absolute necessity both in terms of logistics and in terms of readiness of vendors to support Shibboleth. The ability to seamlessly handle (for the user) certain resources that have been fully "Shibbolized" along side certain resources that still rely on IP-based authentication is why this has been termed a "hybrid" model. And the ability of EZproxy to play traffic cop and decide if a particular connection between user and resource needs to be either (1) proxied (since it is IP-based) or (2) handed off for a direct connection (since it is Shibboleth capable) can be thought of as an "Access Mode Switch" functionality.

Again, this best practice builds on the one before; in order to support it, a vendor must already support best practices #2 and #3.

In order for a resource provider to be Shibboleth/EZproxy hybrid compliant, their Shibboleth authenticated direct links must be either (1) the exact same URL as the unauthenticated link to the resource, or (2) capable of being rewritten consistently from an unauthenticated resource link to a Shibboleth authenticated direct link.

Two examples might make some sense of this:

Example 1:

JSTOR provides persistent URLs such that the same persistent URL that is used by other authentication means (eg. IP authentication) also can be used as the RESOURCE-LOCATION url when creating WAYFless URLs as described above. For instance, <http://www.jstor.org/stable/3912141>, is a persistent link to The Science Newsletter. This same url can be used directly to create a WAYFless URL: <http://www.jstor.org/start-session?entityID=urn:mace:incommon:university.edu&target=http%3A%2F%2Fwww.jstor.org%2Fstable%2F3912141>

The fact that the same URL can be used to create the WAYFless URL, this makes implementation via EZproxy very straightforward. EZproxy provides a mechanism, called SPUEdit, for rewriting URLs and redirecting browsers to the new rewritten URL. This SPUEdit functionality allows EZproxy to create a WAYFless URL from a persistent link. In the case of JSTOR, an SPUEdit directive in EZproxy can be defined as follows:

```
SPUEdit @^https*://.*\.jstor\.org.$@http://www.jstor.org/start-session?entityID=urn:mace:incommon:university.edu&target=$e0@irs
```

The SPUEdit is a regular expression rule. In this example, `^https*://.*\.jstor\.org.$`, is the URL pattern that is matched in the regular expression. And `http://www.jstor.org/start-session?entityID=urn:mace:incommon:university.edu&target=$e0` is the URL that is created from the regular expression. [The `$e0` in this example is the entire matched pattern encoded] When EZproxy processes a URL, for instance,

<http://ezproxy.university.edu/login?url=http://www.jstor.org/stable/3912141>

the URL will match the SPUEdit pattern, and redirect the user's browser through a WAYFless URL:

<http://www.jstor.org/start-session?entityID=urn:mace:incommon:university.edu&target=http%3A%2F%2Fwww.jstor.org%2Fstable%2F3912141>

Example 2:

HW Wilson Web provides persistent URLs. However, the persistent URLs that are used to create WAYFless URLs for HW Wilson Web are not the same persistent URLs that are used by other authentication methods. For instance, a persistent URL for [Visual Arts:the state of the art](#) is

<http://vnweb.hwwilsonweb.com/hww/jumpstart.jhtml?recid=0bc05f7a67b1790e22c948a92294d51df84446d22ac499870f2fecb1b0400d7c102b0ca3d14413a7&fmt=C>.

A Shibboleth authenticated direct link to the same resource though is a different URL structure,

<https://vnweb.hwwilsonweb.com/cgi-bin/shibenv.pl?recid=0bc05f7a67b1790e22c948a92294d51df84446d22ac499870f2fecb1b0400d7c102b0ca3d14413a7&fmt=C>.

Notice that the difference between the two URLs:

<http://vnweb.hwwilsonweb.com/hww/jumpstart.jhtml> <=> <https://vnweb.hwwilsonweb.com/cgi-bin/shibenv.pl>

It turns out that the `jumpstart.jhtml` pattern can be consistently replaced by the `shibenv.pl` pattern across the HW Wilson Web platform in order to create WAYFless URLs. The process is slightly more complicated, but can be handled by a SPUEdit directive in EZproxy:

SPUEdit @^https://vnweb.hwwilsonweb.com/www/jumpstart.jhtml?(.*)\$@https://shib.university.edu/shibboleth-idp/SSO?shire=https%3A%2F%2Fvnweb.hwwilsonweb.com%2FShibboleth.sso%2FSAML%2FPOST&providerId=https%3A%2F%2Fvnweb.hwwilsonweb.com%2Fshibboleth&target=https%3A%2F%2Fvnweb.hwwilsonweb.com%2Fcgi-bin%2Fshibenv.pl%3F\$e1@irs

Notice that, in this case, \$e1 is used instead of \$e0. This is because \$e1 is the portion of the original URL that matches (.*) in the pattern. Basically, this SPUEdit directive replaces the jumpstart.jhtml portion of the URL with the shibenv.pl portion, and then constructs a WAYFless URL.

The importance of this is that it allows libraries to have a single point within the library environment, EZproxy, where WAYFless URLs are created. There are several different use cases within a university and beyond for creating Shibboleth-authenticated direct URLs. As can be imagined, these can be complicated to create by hand, and also complicated for software systems within the university setting (which may or may not even be aware of Shibboleth) to create. However, it is much simpler to create an EZproxy link by simple appending the target URL to the EZproxy login URL.