

Attribute Registry Overview

Version 1.1 of the Attribute Registry is the latest release of one of the early deliverables from the Scalable Privacy project.

The core data elements are attributes, each of which comes from one of a defined set of specifications or standards. The images in this overview were taken directly from the ontology tool, Protégé, used to maintain the registry. A web-accessible version of the registry is available at <http://webprotege.stanford.edu/#Edit:projectId=623e0196-844a-4d86-a65b-b4d2f923ab97>

- Specifications
- Attributes
- Attribute Class
- Future Work
- Reference: The Currently Defined Set of Sixty-one Attribute Classes

Specifications

The screenshot displays the Protégé ontology editor interface. On the left, the 'Class hierarchy: Specification' pane shows a tree structure with 'Thing' as the root, followed by 'Attribute', 'AttributeClass', and 'Specification' (highlighted in blue). The main workspace is divided into two panes: 'Annotations: Specification' (empty) and 'Description: Specification'. The 'Description' pane lists relationships and members. Under 'Members', a list of specifications is shown, each with a diamond icon and three control buttons (question mark, at-sign, and X).

| Specification | ? | @ | X |
|----------------|---|---|---|
| eduCourse | ? | @ | X |
| eduMember | ? | @ | X |
| eduPerson | ? | @ | X |
| FICAM | ? | @ | X |
| IMS_Person | ? | @ | X |
| OpenID_Connect | ? | @ | X |
| OpenSocial | ? | @ | X |
| RFC4524 | ? | @ | X |
| Schac | ? | @ | X |
| SCIM_Core | ? | @ | X |
| VA_EDM | ? | @ | X |
| X.520 | ? | @ | X |

Each attribute of the 715 attributes currently in the registry is associated with the specification that defines it. For example, the OpenID Connect specification covers the following attributes:

Class hierarchy: Sp

- Thing
 - Attribute
 - AttributeClass
 - Specification

Annotations: OpenID_Connect

Annotations +

Description: OpenID_Conn

Types +

- Specification ? @ x o

Same Individual As +

Different Individuals +

Property assertions: OpenID_Connect

Object property assertions +

- specifies oidc-website ? @ x o
- specifies oidc-preferred_username ? @ x o
- specifies oidc-region ? @ x o
- specifies oidc-phone_number ? @ x o
- specifies oidc-formatted ? @ x o
- specifies oidc-middle_name ? @ x o
- specifies oidc-profile ? @ x o
- specifies oidc-nickname ? @ x o
- specifies oidc-gender ? @ x o
- specifies oidc-locality ? @ x o
- specifies oidc-family_name ? @ x o
- specifies oidc-zoneinfo ? @ x o
- specifies oidc-country ? @ x o
- specifies oidc-locale ? @ x o
- specifies oidc-address ? @ x o
- specifies oidc-name ? @ x o
- specifies oidc-picture ? @ x o
- specifies oidc-email_verified ? @ x o
- specifies oidc-user_id ? @ x o
- specifies oidc-street_address ? @ x o
- specifies oidc-email ? @ x o
- specifies oidc-given_name ? @ x o
- specifies oidc-updated_time ? @ x o
- specifies oidc-postal_code ? @ x o
- specifies oidc-birthday ? @ x o

Object property hierarchy

Object property hierarchy

- topObjectProperty
 - classifies
 - isClassifiedBy
 - isSpecifiedBy
 - specifies

Attributes

An example attribute entry in the registry appears as follows (this is the Profile attribute from OpenID Connect):

Description: oidc-profile

Types +

- Attribute ? @ x o

Same Individual As +

Different Individuals +

Property assertions: oidc-profile

Object property assertions +

- isSpecifiedBy OpenID_Connect ? @ x o
- isClassifiedBy Profile ? @ x o

Data property assertions +

- AttributeName "profile"^^string ? @ x o
- SourceLocation "http://openid.net/specs/openid-connect-basic-1_0.html#id_res"^^string ? @ x o
- Syntax "string"^^string ? @ x o
- Section "2.52"^^string ? @ x o
- Definition "URL of the End-User's profile page."^^string ? @ x o

Note the metadata (Object properties and Data properties) recorded in the registry for the Profile attribute. Version 1.0 contains a minimal set of metadata elements. Other types of metadata may be added to suit emerging needs in the attribute ecosystem work.

Another example attribute entry in the registry is eduPersonPrincipalName from the eduPerson specification:

Property assertions: eduPersonPrincipalName

Object property assertions +

- isClassifiedBy Identifier
- isSpecifiedBy eduPerson

Data property assertions +

- SourceLocation "http://macedir.org/specs/eduperson/#eduPersonPrincipalName"^^string
- AttributeName "eduPersonPrincipalName"^^string
- Oid "1.3.6.1.4.1.5923.1.1.1.6"^^string
- Definition "scoped identifier for a person. It should be represented in the form 'user@scope' where 'user' is a name-based identifier for the person and where 'scope' defines a local security domain. Each value of 'scope' defines a namespace within which the assigned identifiers MUST be unique. Given this rule, if two eduPersonPrincipalName (ePPN) values are the same at a given point in time, they refer to the same person"^^string
- Syntax "directoryString"^^string
- Section "2.2.8"^^string

Note the relatively full Definition element in this case. This is drawn from the specification itself.

Attribute Class

At the top of the eduPersonPrincipalName example above, there is the object property "isClassifiedBy" with the value "Identifier". This is an example of a metadata element meant to categorize attributes across specifications into a defined set of types. This metadata element is called "Attribute Class". Here is the first part of a listing of the currently defined attribute classes:

Class hierarchy: Attr

- Thing
 - Attribute
 - AttributeClass
 - Specification

Annotations: AttributeClass

Annotations +

Description: AttributeClass

Members +

- Account
- Address
- Affiliation
- Application
- Assurance
- Birthdate
- BirthPlace
- Citizenship
- Contact
- Country
- Date

A couple examples will clarify the notion of attribute class. Take the example of attributes relating to preferences.

The screenshot shows two panels. The left panel, titled "Description: Preference", lists "Types" as "AttributeClass" and includes options for "Same Individual As" and "Different Individuals". The right panel, titled "Property assertions: Preference", lists "Object property assertions" including "classifies osoc-emails-primary", "classifies osoc-contactPreference", and "classifies r4524-drink". It also lists "Data property assertions", "Negative object property assertions", and "Negative data property assertions".

The Open Social specification (attributes whose prefix is "osoc") contains two attributes in the class "preference". The LDAP specification (currently RFC4524) contains an attribute "drink" which indicates personal preference as well. Here is the preference attribute, osoc-emails-primary:

The screenshot shows two panels. The left panel, titled "Description: osoc-emails-", lists "Types" as "Attribute" and includes options for "Same Individual As" and "Different Individuals". The right panel, titled "Property assertions: osoc-emails-primary", lists "Object property assertions" including "isClassifiedBy Preference" and "isSpecifiedBy OpenSocial". It also lists "Data property assertions" including "AttributeName 'emails-primary'^^string", "Definition 'A Boolean value indicating whether this instance of the Plural Field is the primary or preferred value of for this field, e.g. the preferred mailing address or primary e-mail address. Service Providers MUST NOT mark more than one instance of the same Plural Field as primary='true', and MAY choose not to mark any fields as primary, if this information is not available. For efficiency, Service Providers SHOULD NOT mark all non-primary fields with primary='false', but should instead omit this sub-field for all non-primary instances.'^^string", "Syntax 'Boolean'^^string", "SourceLocation 'http://opensocial-resources.googlecode.com/svn/spec/trunk/Social-Data.xml#Person'^^string", and "Section '2.14'^^string".

Another example of the attribute class metadata is "role". Several specifications (SCIM, SCHAC, LDAP and X.520) contain attributes meant to carry some definition of a person's role:

The image shows a web interface with two main panes. The left pane, titled "Description: Role", contains a "Types" section with a plus icon and a yellow circle next to "AttributeClass". Below this are sections for "Same Individual As" and "Different Individuals", each with a plus icon. The right pane, titled "Property assertions: Role", contains three sections: "Object property assertions" with a plus icon, "Data property assertions" with a plus icon, and "Negative object property assertions" and "Negative data property assertions", each with a plus icon. Under "Object property assertions", there are four entries, each with a blue square icon and a plus icon: "classifies scim-roles", "classifies schacProjectSpecificRole", "classifies r4524-organizationalStatus", and "classifies X520-roleOccupant". Each entry has four circular icons to its right: a question mark, an at-sign, an 'x', and an empty circle.

Future Work

Going forward, attributes from additional specifications and standards will be added (including schema from additional national federations in Norway and Australia). One open issue is whether the current list of attribute metadata is adequate or whether there would be value in carrying additional metadata elements in a general purpose registry of this sort.

Reference: The Currently Defined Set of Sixty-one Attribute Classes

AccessibilityProfile, Account, Address, Affiliation, Age, Anniversary, Application, Assurance
Birthdate, BirthPlace
Certification, Citizenship, Clearance, Contact, Country, Course
DN, Date, DeathDate, Description
Email, EmailMetadata, Entitlement, Ethnicity
Format
Gender, Group
HostName
Identifier
Jurisdiction
Language, Link, Locale, Location
Manager
Name, Note
Operational, Organization
Password, Phone, Photo, PhysicalCharacteristic, Pointer, Position, Preference, Presence, Privacy, Profile
Relationship, Residency, Role
Salutation, Search, StateOrProvince, StatusMessage, SuperiorNode
Tag, Timezone
URL
VitalEvent