

saml-metadata-sp-sso-settings

Jump to:

[AssertionConsumerService endpoint \(ACS URL\) requirements](#) | [Configuring Requested Attributes](#) | [Should I configure a SingleLogout endpoint?](#)

The SP SSO Settings section in Federation Manager is where a Site Administrator configures the key Service Provider (SP) service endpoints found in the SAML metadata's `SPSSODescriptor` element. These include:

- Assertion Consumer Service endpoints (`<AssertionConsumerService>`), also known as ACS URLs
- Discovery Response locations (`<SingleSignOnService>`)
- Requested Attributes (`<RequestedAttribute>` elements within `<AttributeConsumingService>`)
- Single Logout Service endpoints (`<SingleLogoutService>`).

To configure:

Login to Federation as a Site Administrator

Click on the entity you wish to update to bring up the View/Edit page.

On the left navigation, click "SP SSO Settings".

Enter information as directed as shown in the "SP SSO Settings" section.

Click the XML toggle icon to preview the data you've entered as shown in SAML.

Use the toggle in the Index column to manually order your ACS URLs and Discovery Response endpoints.

Working with SAML metadata

- [Signing and Encryption Keys](#)
- [Signaling Encryption Method Support for a Service Provider](#)
- [Entity ID](#)
- [Scope](#)
- [Contacts information](#)
- [Hide an identity provider from discovery](#)
- [IdP SSO Settings \(IDPSSODescriptor\)](#)
- [Requested Attributes](#)
- [User interface elements](#)
- [SP SSO Settings \(SPSSODescriptor\)](#)

Related content

- [Federation Manager](#)
- [Requirements to use Federation Manager](#)
- [Understanding entity status in Federation Manager](#)
- [Reset your Federation Manager user password](#)
- [Add an identity provider](#)
- [Add a service provider](#)
- [Hide an identity provider from discovery](#)
- [User interface elements](#)
- [Declare R and S support for an identity provider](#)
- [Declare Sirtfi compliance](#)

SP SSO Settings (SPSSODescriptor) Collapse All

Assertion Consumer Service Endpoints

Index	Binding	Location	
1	urn:oasis:names:tc:SAML:2.0:bindings:HTTP-POST	https://service1.internet2.edu/Shibboleth.sso/SAML2/POST	Delete
2	urn:oasis:names:tc:SAML:2.0:bindings:HTTP-POST-SimpleSign	https://service1.internet2.edu/Shibboleth.sso/SAML2/POST-SimpleSign	Delete
3	urn:oasis:names:tc:SAML:2.0:bindings:HTTP-Artifact	https://service1.internet2.edu/Shibboleth.sso/SAML2/Artifact	Delete
4	urn:oasis:names:tc:SAML:2.0:bindings:HTTP-POST	https://service8.internet2.edu/Shibboleth.sso/SAML2/POST	Delete
5	urn:oasis:names:tc:SAML:2.0:bindings:HTTP-Artifact	https://service8.internet2.edu/Shibboleth.sso/SAML2/Artifact	Delete
Index: 6	SAML 2.0 HTTP-POST		Add

Discovery Response Locations

Index	Location	
1	https://service1.internet2.edu/Shibboleth.sso/DS	Delete
2	https://service1.internet2.edu/Shibboleth.sso/Login	Delete
Index: 3		Add

Requested Attributes

Required	Name	Values	
<input checked="" type="checkbox"/>	<code>!requestedAttributeFriendlyName="eduPersonPrincipalName" Name="urn:oid:1.3.6.1.4.1.5923.5.1.1.41" NameFormat="urn:oasis:names:tc:SAML:2.0:attr-format:uri"</code>		Delete
<input type="checkbox"/>	givenName		Delete
<input type="checkbox"/>	email		Delete
<input type="checkbox"/>	sn		Delete
<input type="checkbox"/>	displayName		Add

Single Logout Service Endpoints

Binding	Location	
SAML 2.0 HTTP-POST		Add

AssertionConsumerService endpoint (ACS URL) requirements

All `<AssertionConsumerService>` endpoints **MUST** begin with `https://`, that is, an Assertion Consumer Service endpoint, or ACS URL, must be encrypted with modern, supported TLS encryption.

Get help

Can't find what you are looking for?

[help Ask the community](#)

A SP in the Incommon Federation **MUST** include at least one `<AssertionConsumerService>` endpoint with a SAML2 HTTP-POST binding.

DO NOT register any SAML1 endpoints. SAML1 is deprecated. The option is available for legacy support only.

See Section 5.1: Web Browser SSO Profile in the [Security Assertion Markup Language \(SAML\) V2.0 Technical Overview](#).

Should I configure a DiscoveryResponse location?

If you have configured your SP to use a [Discovery Service](#) via the *SAML V2.0 Identity Provider Discovery Protocol*, you **MUST** include at least one `<DiscoveryResponse>` endpoint in your SP metadata. A Discovery Service will redirect the user back to you at the designated endpoint once they have selected their preferred identity provider.

Configuring Requested Attributes

Configuring Requested Attributes is optional.

Federation Manager lets you select from a list of commonly supported attributes in the Incommon Federation when configuring Requested Attributes.

To learn more, see [Requested Attributes](#).

Should I configure a SingleLogout endpoint?

If you have configured your SP to send single logout (SLO) requests to an IdP advertising a SingleLogoutService endpoint, you must publish your SP's SingleLogoutService endpoint in your published metadata. Failing to do so will cause an error when the IdP attempts to respond to your SP's SLO request.

Shibboleth SP software is by default configured to send SLO requests.