

cm_env_sources

Table	cm_env_sources
Description	Env Organizational Identity Sources
Plugin	Env Source

Column	Format	Description	Definition	Comments
id	integer, primary key	Row identifier	autoincrement	
org_identity_source_id	integer, foreign key	Organizational Identity Source ID	cm_org_identity_sources :id	
duplicate_mode	varchar(2)	Duplicate handling mode	- AI: Any Identifier - LI: Login Identifier - SI: SOR Identifier	Added in Registry v4.1.0
sp_type	varchar(2)	Web Server SP Provider	- SH: Shibboleth SP - SS: SimpleSamlPHP SP - O: Other	Added in Registry v4.3.0
redirect_on_duplicate	varchar(1024)	Redirect target on duplicate		Added in Registry v4.1.0
env_name_honorific	varchar(80)	Environment variable holding official honorific	cm_names	
env_name_given	varchar(80)	Environment variable holding official given name	cm_names	
env_name_middle	varchar(80)	Environment variable holding official middle name	cm_names	
env_name_family	varchar(80)	Environment variable holding official family name	cm_names	
env_name_suffix	varchar(80)	Environment variable holding official suffix	cm_names	
env_affiliation	varchar(80)	Environment variable holding affiliation	cm_co_person_roles	
env_title	varchar(80)	Environment variable holding title	cm_co_person_roles	
env_o	varchar(80)	Environment variable holding organization	cm_co_person_roles	
env_ou	varchar(80)	Environment variable holding department	cm_co_person_roles	
env_mail	varchar(80)	Environment variable holding official email address	cm_email_addresses	
env_telephone_number	varchar(80)	Environment variable holding office telephone number	cm_telephone_numbers	
env_address_street	varchar(80)	Environment variable holding office street	cm_addresses	
env_address_locality	varchar(80)	Environment variable holding office locality/city	cm_addresses	
env_address_state	varchar(80)	Environment variable holding office state	cm_addresses	
env_address_postalcode	varchar(80)	Environment variable holding office postal code	cm_addresses	
env_address_country	varchar(80)	Environment variable holding office country	cm_addresses	
env_identifier_eppn	varchar(80)	Environment variable holding eppn	cm_identifiers	
env_identifier_eppn_login	boolean	Whether eppn should be allowed to login to Registry	cm_identifiers	
env_identifier_eptid	varchar(80)	Environment variable holding eptid	cm_identifiers	
env_identifier_eptid_login	boolean	Whether eptid should be allowed to login to Registry	cm_identifiers	
env_identifier_epuid	varchar(80)	Environment variable holding epuid	cm_identifiers	
env_identifier_epuid_login	boolean	Whether epuid should be allowed to login to Registry	cm_identifiers	
env_identifier_orcid	varchar(80)	Environment variable holding orcid	cm_identifiers	
env_identifier_orcid_login	boolean	Whether orcid should be allowed to login to Registry	cm_identifiers	
env_identifier_sorid	varchar(80)	Environment variable holding sorid	cm_identifiers	
env_identifier_sorid_login	boolean	Whether sorid should be allowed to login to Registry	cm_identifiers	
env_identifier_network	varchar(80)	Environment variable holding network	cm_identifiers	
env_identifier_network_login	boolean	Whether network should be allowed to login to Registry	cm_identifiers	