

Improve GSH

Wiki Home	Deploying Grouper	Grouper Guides	Grouper Deployment Guide	Community Contributions	Internal Developer Resources
---------------------------	-----------------------------------	--------------------------------	--	---	--

- Grouper 2.3 uses BeanShell. There's no tab completion, history, etc.
- Grouper 2.3 with patches and Grouper 2.4+ switches to Groovy as the default shell.
- The goal was to keep any existing GSH scripts that deployers may have written as compatible as possible with the [new Groovy based GSH](#).
- Built in GSH commands (e.g. obliterateStem) were modified to work with both BeanShell and Groovy.
- There's an option to switch back to BeanShell by specifying the following in grouper.properties

```
gsh.useLegacy = true
```

- gsh.sh and gsh.bat were not changed.
- Users can still use another shell as they did before (e.g. <https://github.com/wgthom/groovysh4grouper>)

This is how [GSH](#) would start up before the 2.3 patch that contains this change (with an example built in gsh command - obliterateStem). (There's no change.):

```
shilen@Shilens-MacBook-Pro-2 grouper (GRP-1553) $ ./bin/gsh.sh
Using GROUPER_HOME: /Users/shilen/Desktop/internet2/github2/grouper
Using GROUPER_CONF: /Users/shilen/Desktop/internet2/github2/grouper/conf
Using JAVA: java
using MEMORY: 64m-750m
Grouper starting up: version: 2.3.0, build date: 2017/06/02 16:18:52, env: <no label configured>
grouper.properties read from: /Users/shilen/Desktop/internet2/github2/grouper/conf/grouper.properties
Grouper current directory is: /Users/shilen/Desktop/internet2/github2/grouper
log4j.properties read from: /Users/shilen/Desktop/internet2/github2/grouper/conf/log4j.properties
Grouper is logging to file: /Users/shilen/Desktop/internet2/github2/grouper/logs/grouper_error.log, at min
level WARN for package: edu.internet2.middleware.grouper, based on log4j.properties
grouper.hibernate.properties: /Users/shilen/Desktop/internet2/github2/grouper/conf/grouper.hibernate.properties
grouper.hibernate.properties: sa@jdbc:hsqldb:hsqldb://localhost:9001/grouper
subject.properties read from: /Users/shilen/Desktop/internet2/github2/grouper/conf/subject.properties
sources.xml read from: /Users/shilen/Desktop/internet2/github2/grouper/conf/sources.xml
sources configured in: sources.xml
sources.xml      grouper source id: g:gsa
sources.xml      grouper source id: grouperEntities
sources.xml      jdbc source id: jdbc: GrouperJdbcConnectionProvider
Grouper warning: jarfile mismatch, expecting name: 'subject.jar' size: LinkedHashSet size: 2: [0]: 271917
[1]: 266056
manifest version: 2.2.0. However the jar detected is: /Users/shilen/Desktop/internet2/github2/grouper/lib
/grouper/subject.jar, name: subject.jar size: 271917 manifest version: 2.3.0
Type help() for instructions
gsh 0% obliterateStem("etc:grouperUi", true, true)
Would obliterate stem: etc:grouperUi
Would be done deleting group: etc:grouperUi:grouperUiUserData
Would be done obliterating stem: etc:grouperUi
true
gsh 1%
```

And after the patch to use Groovy:

```

shilen@Shilens-MacBook-Pro-2 grouper (GRP-1553) $ ./bin/gsh.sh
Using GROUPER_HOME: /Users/shilen/Desktop/internet2/github2/grouper
Using GROUPER_CONF: /Users/shilen/Desktop/internet2/github2/grouper/conf
Using JAVA: java
using MEMORY: 64m-750m
Grouper starting up: version: 2.3.0, build date: 2017/06/02 16:18:52, env: <no label configured>
grouper.properties read from: /Users/shilen/Desktop/internet2/github2/grouper/conf/grouper.properties
Grouper current directory is: /Users/shilen/Desktop/internet2/github2/grouper
log4j.properties read from: /Users/shilen/Desktop/internet2/github2/grouper/conf/log4j.properties
Grouper is logging to file: /Users/shilen/Desktop/internet2/github2/grouper/logs/grouper_error.log, at min
level WARN for package: edu.internet2.middleware.grouper, based on log4j.properties
grouper.hibernate.properties: /Users/shilen/Desktop/internet2/github2/grouper/conf/grouper.hibernate.properties
grouper.hibernate.properties: sa@jdbc:hsqldb:hsqldb://localhost:9001/grouper
subject.properties read from: /Users/shilen/Desktop/internet2/github2/grouper/conf/subject.properties
sources.xml read from: /Users/shilen/Desktop/internet2/github2/grouper/conf/sources.xml
sources configured in: sources.xml
sources.xml      grouper source id: g:gsa
sources.xml      grouper source id: grouperEntities
sources.xml      jdbc source id: jdbc: GrouperJdbcConnectionProvider
Grouper warning: jarfile mismatch, expecting name: 'subject.jar' size: LinkedHashSet size: 2: [0]: 271917
[1]: 266056
manifest version: 2.2.0. However the jar detected is: /Users/shilen/Desktop/internet2/github2/grouper/lib
/grouper/subject.jar, name: subject.jar size: 271917 manifest version: 2.3.0
Type help() for instructions
Groovy Shell (2.4.11, JVM: 1.8.0_121)
Type ':help' or ':h' for help.
-----
-----
-----
groovy:000> :load /Users/shilen/Desktop/internet2/github2/grouper//conf/groovysh.profile
groovy:000> obliterateStem("etc:grouperUi", true, true)
Would obliterate stem: etc:grouperUi
Would be done deleting group: etc:grouperUi:grouperUiUserData
Would be done obliterating stem: etc:grouperUi
==> true
groovy:000>

```

(That first load command is done automatically on start up.)

Also, other parameters to gsh (e.g. -registry, -runarg, etc) continue working as before.

And normal Java calls continue to work as well, e.g.

```

groovy:000> grouperSession = GrouperSession.startRootSession()
==> 5c455cfc3511413abdb20276c45f8d7d, 'GrouperSystem', 'application'
groovy:000> new GroupSave(grouperSession).assignName("stem1:a").assignCreateParentStemsIfNotExist(true).save();
==> Group[name=stem1:a, uuid=535a12b070e54474bf67f0e538adebe8]
groovy:000>

```

See also

Grouper Shell