# **Hide from Discovery category**

#### Jump to:

Why use the Hide from Discovery category?

The "Hide from Discovery" entity category is a category of Identity Providers that are intended **not to be shown on discovery interfaces** by default.



#### **Hide From Discovery Category Specification**

InCommon's implementation of the *Hide from Discovery category* and the use of the hide-from-discovery entity attribute (described below) conform to the REFEDS Hide from Discovery category specification.

The hide-from-discovery entity attribute is self-asserted by IdP operators but InCommon Operations may insert the hide-from-discovery entity attribute into any IdP entity descriptor at its discretion.

## Why use the Hide from Discovery category?

By and large, participants register an IdP for one or more of the following reasons:

- 1. To interoperate with providers of commercial vendor services called *Sponsored Partners*
- 2. To interoperate with Enterprise Services (co-located in the same security domain as the IdP)
- To interoperate with cross-domain Federation Services such as Research & Scholarship Category services and other collaborative services

To interoperate with Sponsored Partners and Enterprise Services, a bilateral arrangement is often needed, whereas cross-domain Federation Services are "promiscuous" in the sense that they are willing and able to interoperate with **any** IdP. This gives rise to *IdP Discovery*, a user-driven process (or interface) to discover the federated user's preferred IdP.

An IdP that interoperates solely with Sponsored Partners and/or Enterprise Services may not need (or want) to be exposed on arbitrary discovery interfaces, in which case the IdP should declare the hide-from-discovery entity attribute in metadata. Federation Services can (and should) filter such IdPs from their discovery interfaces.

Be aware that InCommon Operations reserves the right to insert the hide-from-discovery entity attribute into any IdP entity descriptor at its discretion. Possible reasons include, but are not limited to:

- The IdP is known not to consume InCommon metadata on a daily basis.
- The IdP is in a domain name that is not public.
- The IdP has endpoints that are behind a firewall.

### Asserting Hide from Discovery

An IdP calls out its desire to *Hide From Discovery* by asserting the following entity attribute in metadata (whitespace added for readability):

```
<mdattr:EntityAttributes
xmlns:mdattr="urn:oasis:names:tc:SAML:metadata:attribute">
<saml:Attribute
xmlns:saml="urn:oasis:names:tc:SAML:2.0:assertion"
NameFormat="urn:oasis:names:tc:SAML:2.0:attrname-format:uri"
Name="http://macedir.org/entity-category">
<saml:AttributeValue>
http://refeds.org/category/hide-from-discovery
</saml:AttributeValue>
</saml:AttributeValue>
</mdattr:EntityAttributes>
```

To assert the hide-from-discovery entity attribute in IdP metadata, a Site Administrator signs into the Federation Manager to make the updates. See the Hide an identity provider from discovery topic to learn how

### For More Information

### Related content

- Sirtfi category
- Registered by InCommon category
- InCommon-Only Research and Scholarship category (deprecated)
- REFEDS Research and Scholarship category
- Review and submit metadata
- Tagging an entity with Research and Scholarship entity attribute
- Research and Scholarship FAQ
- Introduction to Federation Manager
- Hide an identity provider from discovery
- Understanding entity status in Federation Manager

### Get help

Can't find what you are looking for?

help Ask the community

• https://wiki.shibboleth.net/confluence/display/SHIB2/NativeSPMetadataProvider