

cm_co_jira_provisioner_targets

Table	cm_co_jira_provisioner_targets
Description	Per-CO Jira provisioning target configurations
Plugin	Jira Provisioning Plugin

Column	Format	Description	Definition	Comments
id	integer, primary key	Row identifier	autoincrement	
co_provisioning_target_id	integer, foreign key	CO Provisioning Target ID	cm_co_provisioning_targets :id	
server_id	integer, foreign key	Server ID	cm_servers :id	
username_type	varchar(64)	Type of identifier to use as Jira person name	cm_identifiers :type	
query_by_username	boolean	Query Jira using both key and username	- true: Query using both key and username - false: Query only using key	
provision_co_group_id	integer, foreign key	If set, the ID for the CO Group to which a person must belong to be provisioned to Jira	cm_co_groups :id	
deactivate	boolean	Whether users in Jira are deleted or set to inactive	- true: user set to inactive in Jira - false: user deleted in Jira	
group_type	varchar(64)	If set, only CO Groups with this Identifier type will be provisioned	cm_identifiers :type	
group_name	boolean	Whether to use the value of the group_type identifier as the name of the group in Jira	- true: the value of the Identifier will be used as the group name in Jira - false: the name of the CO Group in Registry will be used as the group name in Jira	
remove_unknown	boolean	Whether to remove unknown users from groups in Jira	- true: users unknown to Registry will be removed from groups in Jira - false: users unknown to Registry will not be removed from groups in Jira	