

Identifier Schema

Attributes

- **Version:** 1.0
- Defined types are as configured at a platform (when attached to an Org Identity) or CO (when attached to a CO Person or CO Department) level. CO-specific types can be determined via the [CoExtendedType API](#).
- See [cm_identifiers](#) for definitions of other attributes and elements

JSON Request

```
{
  "RequestType": "Identifiers",
  "Version": "1.0",
  "Identifiers": [
    {
      "Version": "1.0",
      "Type": "<Type>",
      "Identifier": "<Identifier>",
      "Login": true|false,
      "Person": { "Type": ("CO"|"Dept"|"Group"|"Org"|"Organization"), "Id": "<ID>" },
      "CoProvisioningTargetId": "<CoProvisioningTargetId>",
      "Status": "Active"|"Deleted"
    }
  ]
}
```

JSON Request (Assignment)

```
{
  "RequestType": "Identifiers",
  "Version": "1.0",
  "Identifiers": [
    {
      "Version": "1.0",
      "Person": { "Type": ("CO"|"Dept"|"Group"), "Id": "<ID>" }
    }
  ]
}
```

XML Request

```
<!ELEMENT Identifiers (Identifier)>
<!ATTLIST Identifiers Version CDATA #FIXED "1.0">
<!ELEMENT Identifier (Type,Identifier,Login,Person)>
<!ATTLIST Identifier Version CDATA #FIXED "1.0">
<!ELEMENT Type (#PCDATA)>
<!ELEMENT Identifier (#PCDATA)>
<!ELEMENT Login (True|False)>
<!ELEMENT Person (Type,Id)>
  <!ELEMENT Person Type (CO|Dept|Group|Org|Organization)>
  <!ELEMENT Person Id ID>
<!ELEMENT CoProvisioningTargetId (#PCDATA)>
<!ELEMENT Status (Active|Deleted)>
```

XML Request (Assignment)

```

<!ELEMENT Identifiers (Identifier)>
<!--ATTLIST Identifiers Version CDATA #FIXED "1.0"-->
<!ELEMENT Identifier (Person)>
<!--ATTLIST Identifier Version CDATA #FIXED "1.0"-->
<!ELEMENT Person (Type,Id)>
  <!--ELEMENT Person Type (CO|Dept|Group)>
  <!--ELEMENT Person Id ID>

```

JSON Response

```

{
  "ResponseType": "Identifiers",
  "Version": "1.0",
  "Identifiers": [
    {
      "Version": "1.0",
      "Id": "<ID>",
      "Type": "<Type>",
      "Identifier": "<Identifier>",
      "Login": true|false,
      "Person": { "Type": ("CO"|"Dept"|"Group"|"Org"|"Organization"), "ID": "<ID>" },
      "CoProvisioningTargetId": "<CoProvisioningTargetId>",
      "Status": "Active"|"Deleted",
      "Created": "<CreateTime>",
      "Modified": "<ModTime>"
    },
    { ... }
  ]
}

```

XML Response

```

<!--ELEMENT Identifiers (Identifier+)-->
<!--ATTLIST Identifiers Version CDATA #FIXED "1.0"-->
<!--ELEMENT Identifier (Type,Identifier,Login,Person)-->
<!--ATTLIST Identifier Version CDATA #FIXED "1.0"-->
<!--ATTLIST Identifier Id ID-->
<!--ELEMENT Type (#PCDATA)-->
<!--ELEMENT Identifier (#PCDATA)-->
<!--ELEMENT Login (True|False)-->
<!--ELEMENT Person (Type,Id)-->
  <!--ELEMENT Person Type (CO|Dept|Group|Org|Organization)-->
  <!--ELEMENT Person Id ID-->
<!--ELEMENT CoProvisioningTargetId (#PCDATA)-->
<!--ELEMENT Status (Active|Deleted)-->
<!--ELEMENT Created (#PCDATA)-->
<!--ELEMENT Modified (#PCDATA)-->

```