

Name API v2

- [Attributes](#)
 - [Sample Record](#)
- [Supported Filters](#)
 - [View \(all\)](#)
 - [Example: Obtain Names for the specified Person](#)
- [Implementation Notes](#)

Resource	Names
URL	/api/v2/names
Supported Standard Operations	<ul style="list-style-type: none">• Add• Delete• Edit• View (one)• View (all)

Attributes

See [names](#) for definitions of attributes.

Additionally, the virtual field *full_name* is included in View operations. This field will hold the display name if set ([AR-Name-2](#)), or a language specific rendering if not ([AR-Name-3](#)). This field is read only.

Sample Record

```
{
  "type_id": 168,
  "person_id": 25,
  "external_identity_id": null,
  "source_name_id": null,
  "honorific": null,
  "given": "Test",
  "middle": "J",
  "family": "Testington",
  "suffix": "V",
  "language": null,
  "primary_name": true,
  "display_name": "TJ Testington",
  "full_name": "TJ Testington"
}
```

Supported Filters

⚠ Viewing all names without an additional filter is not supported.

View (all)

Additional filters:

- external_identity_id
- person_id

Example: Obtain Names for the specified Person

```
GET /registry/api/v2/names?person_id=2400
```

Implementation Notes

- Permitted and required fields are [governed by CO Settings](#).
- The record is read only if `source_name_id` is not null.