

cm_cmp_enrollment_configurations

Table	cm_cmp_enrollment_configurations
Description	CMP enrollment configuration

- Although the data model permits multiple CMP enrollment configurations to be defined, CManage Registry currently only permits one active configuration for the platform.
- There is no REST interface to this table since it is intended to configure the CManage Registry UI.
- CO enrollment flows are handled via [cm_co_enrollment_flows](#).

Column	Format	Description	Definition	Comments
id	integer, primary key	Row identifier	autoincrement	
name	varchar (128)	Configuration Name		
attrs_from_ldap	boolean	Should CMP enrollment attempt to pull attributes from an organizational LDAP server before prompting for attributes?	<ul style="list-style-type: none"> • true: CMP enrollment attempts to query for LDAP attributes • false: CMP enrollment does not query LDAP 	Deprecated
attrs_from_saml	boolean	If the enrollee must authenticate, should CMP enrollment attempt to extract attributes from a SAML assertion before prompting for attributes?	<ul style="list-style-type: none"> • true: CMP enrollment attempts to extract SAML attributes • false: CMP enrollment does not examine SAML attributes 	Deprecated
attrs_from_env	boolean	Should organizational identity attributes be extracted from the server environment? (eg: those that might be set by the web server auth module.)	<ul style="list-style-type: none"> • true: Accept server environment variables as a source of organizational identity • false: Do not accept server environment variables as a source of organizational identity 	
attrs_from_coef	boolean	Should CO enrollment flows be able to prompt for organizational identity attributes? (These attributes will be considered less authoritative than if they had been obtained via LDAP or SAML.)	<ul style="list-style-type: none"> • true: CO enrollment may prompt for organizational identity attributes • false: CO enrollment may not prompt for organizational identity attributes 	
pool_org_identities	boolean	Should organizational identities be pooled and made available to all COs on the CMP?	<ul style="list-style-type: none"> • true: All org identities are available to all COs • false: Org identities are only available to the CO that invoked the enrollment 	See CO-193 for additional information
sponsor_enroll	boolean	Do enrollees need to have a sponsor to enroll?	<ul style="list-style-type: none"> • true: must have a sponsor to enroll • false: sponsor not necessary 	Not implemented
sponsor_active	boolean	Do enrollees need to have a sponsor to stay enrolled?	<ul style="list-style-type: none"> • true: must have a sponsor to stay enrolled • false: sponsor not necessary 	Not implemented
eds_help_url	varchar (256)	For the Shibboleth Embedded Discovery Service, the help URL to publish		
eds_preferred_idps	text(4000)	For the Shibboleth Embedded Discovery Service, the entityIds to always show (one per line)		
eds_hidden_idps	text(4000)	For the Shibboleth Embedded Discovery Service, the entityIds to hide (one per line)		
redirect_on_logout	varchar (1024)	Redirect URL when user logs out		Added in Registry v4.0.0

app_base	varchar (64)	Cached application base for use in generating notification URLs		Added in Registry v4.0.0
status	varchar(2)	Configuration status	<ul style="list-style-type: none">• A: Active• S: Suspended	Only one CMP configuration may be active