Attribute Definition Name Delete

Grouper Web Services

Description

Delete attribute definition names based on name or ID. This is new as of Grouper v2.1

Features

- Delete attribute definition name based on name or ID
- Non-lite service can delete multiple attributeDefNames at once
- Can pass in a txType so that you can run all the deletes in one transaction, or just finish the work that is possible with no enclosing transaction
- Returns attribute definition name(s), and the result code of if it was deleted or not (still a success if it didnt exist, though if the folder didnt exist, that is bad)
- Can actAs another user

attributeDefNameDelete Lite service

- Accepts one attribute def name to delete...
- Documentation: SOAP (click on attributeDefNameDeleteLite), REST (click on attributeDefNameDeleteLite)
- For REST, the request can put data in query string (in URL or request body)
- REST request (colon is escaped to %3A): DELETE /grouper-ws/servicesRest/v2_1_000/attributeDefNames
    - Note: if passing data in request body e.g. actAs, use a POST
- (see documentation above for details): Request object, response object
- Response codes
- Samples (all files with "Lite" in them, click on "download" to see file)

attributeDefNameDelete service

- Accepts multiple attributeDefNames to delete
- Documentation: SOAP (click on attributeDefNameDelete), REST (click on attributeDefNameDelete)
- REST request (colon is escaped to %3A): POST /grouper-ws/servicesRest/v2_1_000/attributeDefNames
- (see documentation above for details): Request object, response object
- Response codes
- Returns an overall status, and a status for each assignment
- Samples (all files without "Lite" in them, click on "download" to see files)