

Attribute Definition Delete

Wiki Home	Deploying Grouper	Grouper Guides	Grouper Deployment Guide	Community Contributions	Internal Developer Resources
---------------------------	-----------------------------------	--------------------------------	--	---	--

[Grouper Web Services](#)

Description

Delete attribute definitions based on name or ID. This is new as of Grouper v2.3.0

Features

- Delete an attribute definition
- Lookup the attribute definition by name, id, or index
- Non-lite service can delete multiple attributeDef at once
- Can pass in a txType so that you can run all the deletes in one transaction, or just finish the work that is possible with no enclosing transaction
- Returns attribute definition(s), and the result code of if it was deleted
- Can actAs another user

attributeDefDelete Lite service

- Accepts one attribute def to delete...
- Documentation: [SOAP](#) (click on attributeDefDeleteLite), [REST](#)
- For REST, the request can put data in query string (in URL or request body)
- REST request (colon is escaped to %3A): DELETE /grouper-ws/servicesRest/v2_3_000/attributeDefs
 - Note: if passing data in request body e.g. actAs, use a POST
- (see documentation above for details): [Request object](#), [response object](#)
- [Response codes](#)
- [Samples](#) (all files with "Lite" in them, click on "download" to see file)

attributeDefDelete service

- Accepts multiple attributeDefs to delete
- Documentation: [SOAP](#) (click on attributeDefDelete), [REST](#)
- REST request (colon is escaped to %3A): DELETE /grouper-ws/servicesRest/v2_3_000/attributeDefs
- (see documentation above for details): [Request object](#), [response object](#)
- [Response codes](#)
- Returns an overall status, and a status for each delete
- [Samples](#) (all files with "Lite" in them, click on "download" to see file)